

OPzV 2V Cells

Type	Positive plate Size (Ah)	Capacity (Ah) C ₁₀ V/Cell (1.80 Vpc at 20°C)	Maximum cell dimensions (mm)					Weight (kg)	Circuit current (A)
			a	b	h1	h2	e		
4 OPzV 200	50	213	103	206	354	378	-	19.5	2010
5 OPzV 250		267	124	206	354	378	-	23.5	2470
6 OPzV 300		319	145	206	354	378	-	28.0	2930
5 OPzV 350	70	383	124	206	471	495	-	31.0	3080
6 OPzV 420		453	145	206	471	495	-	36.5	3880
7 OPzV 490		520	166	206	471	495	-	42.0	4080
6 OPzV 600	100	654	145	206	643	667	-	50.0	4170
8 OPzV 800		891	191	210	644	668	80	68.0	5840
10 OPzV 1000		1105	233	210	646	670	110	82.0	7170
12 OPzV 1200	125	1340	275	210	645	669	140	97.0	8540
12 OPzV 1500		1611	275	210	796	820	140	120.0	9360
16 OPzV 2000		2148	399	214	771	795	2 x 110	165.0	12200
20 OPzV 2500	125	2687	487	212	769	793	3 x 110	200.0	15190
24 OPzV 3000		3326	576	212	769	793	3 x 140	240.0	18300