

VRLA SPG BATTERIEN									
PRODUKTSORTIMENT									
Batterie Typ	Nominal	Nominale Kapazität	Abmessungen (mm)				Gewicht (kg)	Anschluss	
	Spannung (V)	(W/cell) 10min bei 1,60Vpc	Länge	Breite	Höhe (Gehäuse)	Höhe (Gesamtmaß)		Position	Typ
<u>SPG 12-18*</u>	12	15,4	181	76	167	164	5,90	B	M5
<u>SPG 12-28*</u>	12	24,8	168	178	124	115	8,80	B	M5
<u>SPG 12-33*</u>	12	30,7	195	130	160	154	10,90	A	M6
<u>SPG 12-44*</u>	12	38,0	198	167	157	158	14,00	B	M6
<u>SPG 12-55*</u>	12	49,3	229	138	213	214	17,50	A	M6
<u>SPG 12-70*</u>	12	62,6	260	168	211	212	21,50	A	M6
<u>SPG 12-80*</u>	12	73,2	260	168	211	212	23,30	A	M6
<u>SPG 12-100*</u>	12	87,0	306	168	211	212	28,40	A	M6
<u>SPG 12-110*</u>	12	100,5	329	173	209	210	32,20	A	M6
<u>SPG 12-120*</u>	12	109,0	408	176	227	206	35,40	A	M6
<u>SPG 12-135*</u>	12	132,0	342	173	283	286	39,80	B	M6
<u>SPG 12-150*</u>	12	139,0	482	170	242	228	44,30	A	M6
<u>SPG 12-200*</u>	12	187,0	520	240	220	225	66,00	D	M8
<u>SPG 12-230*</u>	12	214,0	521	269	203	208	71,00	D	M8

*TECHNISCHE INFORMATIONEN